

GLINT

ELECTRICAL DISCHARGE MACHINES



CONDE INTERNATIONAL CO., LTD.

GLINT

ELECTRICAL DISCHARGE MACHINES



CONDE INTERNATIONAL CO., LTD.

GLINT

ELECTRICAL DISCHARGE MACHINES



CONDE INTERNATIONAL CO., LTD.



C45 + 75A + D600L

Specification of Machine		C45	Power supply box size	75A	
Working tank capacity	mm	1280 × 800 × 500	Max. processing current	A	75
Working table area	mm	800 × 500	Input power	KVA	8
Working table horizontal travel X-axis	mm	500	Max. processing speed	g/mm	12
Working table vertical travel Y-axis	mm	400	Electrode consumption rate	%	0.3
Spindle travel Z-axis	mm	250 + 350 Powered by electricity	Best surface precision	μ/RMAX	0.3-0.5
Spindle bottom to working table surface	mm	250-850	Net weight	kg	220
Electrode loading weight	kg	250	Packing size	mm	700 × 670 × 1890
Machine N.W.	kg	1800			
Packing size	mm	1700 × 1400 × 2250			
Dielectric unit size	mm	1400 × 1000 × 450	volume		600ℓ
Packing size	mm	1400 × 1000 × 1150	Net weight	kg	280





C45 + 75A + D600L

Specification of Machine		C45	Power supply box size	75A	
Working tank capacity	mm	1280 × 800 × 500	Max. processing current	A	75
Working table area	mm	800 × 500	Input power	KVA	8
Working table horizontal travel X-axis	mm	500	Max. processing speed	g/mm	12
Working table vertical travel Y-axis	mm	400	Electrode consumption rate	%	0.3
Spindle travel Z-axis	mm	250 + 350 Powered by electricity	Best surface precision	μ/RMAX	0.3-0.5
Spindle bottom to working table surface	mm	250-850	Net weight	kg	220
Electrode loading weight	kg	250	Packing size	mm	700 × 670 × 1890
Machine N.W.	kg	1800			
Packing size	mm	1700 × 1400 × 2250			
Dielectric unit size	mm	1400 × 1000 × 450	volume		600ℓ
Packing size	mm	1400 × 1000 × 1150	Net weight	kg	280

